

VinTech RS-CH852H7C33-AP



Model Number	VinTech RS-CH852H7C33-AP
Image Sensor	1/2.7" 5MP
Max. Resolution	2592(H)×1944(V)
Shutter Time	1/5 ~ 1/20000s
Min. Illumination	AGC On: Color: 0.5 lux, B/W : 0.05 lux, 0 lux with IR
IR Leds	10 (4+6)
Focal Length	4.3-141.9mm
Aperture Range	F1.6-F4.3
Horizontal Field of View	H: 59 (W) -2.4 (T)
Optical Zoom	x33
Focus Mode	Auto/Semiauto/Manual
Zoom Speed	<6s (Optical,wide to tele)
Movement Range(Pan)	360°endless
Movement Range(Tilt)	-10°~90° (Auto Flip)
Preset Speed	200°
Preset Positions	255
Pan Speed	0.6°~200°/S
Tilt Speed	0.6°~100°/S
Watch Points	255

Auto Cruise	1
Tour	4
Line scan	1
Pattern scan	4
Protocols	PTZ_PELCO_D, PTZ_PELCO_P
Video Compression	H.264&H.265
Day & Night	Auto/Color/B&W/Schedule
Exposure Mode	Auto/Manual/Shutter First/Iris First
BLC	Support
WDR	Support
HLC	Support
White Balance	Auto/Manual/Outdoor
AGC	Support
Noise	2D&3D
Brightness	Support
Contrast	Support
Saturation	Support
3D Zoom In	Support
Intelligent	PID/LCD/SOD/PD&VD/FD/CC/SOD
ROI	Support
Smart Defog	Support
Digital Zoom	Support
Privacy Zone Cover	Support
Audio Compression	G.711alaw/G.711ulaw/G726.16K/AAC
API Interface	Support
Network Interface	10/100Mbps ethernet interface
Network Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE,SMTP,NTP,UPnP,SNMP,HTTPS,FTP,
online user	5
Browser	IE8 above
Audio Input	1 Line-in
Audio Output	1 Line-out
Alarm Input	1 Input
Alarm Output	1 Output
CVBS	Support
SD Record	Max. 128G

RS485	1
Power Supply	AC24/DC12V/POE+
Working Humidity	< 90%(outdoor)
Working Temperature	-30℃~+60℃
Water Proof	IP66
Dimension	333.4*206.44*351.82/mm